

Manitou System Manager Services

12/21/2023 6:54 pm EST

Contents

[Logger](#)
[Log Viewer](#)
[Broker](#)
[Sentry](#)
[Application Server](#)
[Auto Client](#)
[Marshaller](#)
[Signal Handler](#)
[FEP \(Front End Processor\)](#)
[Overdue Checker](#)
[Report Server](#)
[Report Scheduler](#)
[Publisher](#)
[Router](#)
[IP Receiver](#)
[Web Gateway](#)
[Watchdog](#)
[License Manager](#)
[Telephony Server \(PBX\)](#)
[Media Gateway](#)
[Location Server](#)

Logger

Traces all the events on the system. If this item fails it is not vital to the system and doesn't prevent alarm handling. However, it is important to get the logger restarted as soon as possible for issue tracking purposes.

[Return to Contents](#)

Log Viewer

A diagnostic tool used to watch information as it occurs, such as server calls, error messages, and other activity in the Manitou system. (This does NOT have to run all the time)

[Return to Contents](#)

Broker

Serves as the "brains" of Manitou. It controls communication between the other components, holds global information,

verifies licensing, manages alarm tracking and controls record locking.

[Return to Contents](#)

Sentry

Controls access to Manitou. This provides access tokens to the Application server once the Broker has verified the licensing allows access.

[Return to Contents](#)

Application Server

Works on behalf of the client to access the database, apply business rules and cached data.

[Return to Contents](#)

Auto Client

Acts as the “Virtual Operator” and performs any Operator functions that do not require human intervention.

[Return to Contents](#)

Marshaller

Controls the distribution of signals to the Signal Processor.

[Return to Contents](#)

Signal Handler

Takes incoming signals from the Marshaller and manages proper signal processing into the database.

[Return to Contents](#)

FEP (Front End Processor)

Responsible for receiving, and acknowledging, signals from the receivers and formatting them for interpretation by the Signal Handler. Signals are then translated from various formats to a standard format used by Manitou. Each signal is also stored locally by the FEP, in what is called the FEP debug file. This is only kept for a short period of days. This prevents the loss of signals due to the failure of other system components.

[Return to Contents](#)

Overdue Checker

Responsible for verifying that schedules and test timers are in compliance and that temporary schedules, paged contacts and out-of-service records are cleared once expired.

[Return to Contents](#)

Report Server

Responsible for running the reports at the prompt of the Application Server, when reports are run ad hoc (one-off), or when notified by the Report Scheduler.

[Return to Contents](#)

Report Scheduler

Notifies the Report Server to run reports.

[Return to Contents](#)

Publisher

Distributes all information external to the central station. This may include alphanumeric pages, faxes, emails, or printed reports. This is not an element of the Media Gateway.

[Return to Contents](#)

Router

If accounting software, such as SedonaOffice, is integrated with Manitou, the Router handles the information (such as customer details) linked between Manitou and SedonaOffice.

[Return to Contents](#)

IP Receiver

Software that runs as a Windows service and takes the place of a physical alarm receiver. The IP Receiver communicates using a TCP/IP connection over a network. The IP Receiver is used for card access systems.

[Return to Contents](#)

Web Gateway

The link through which the BoldNet server may connect to Manitou. This may only run on one server at a time.

[Return to Contents](#)

Watchdog

Sends audio and visual alerts to Manitou users.

[Return to Contents](#)

License Manager

This is in place to allow for us to update your license as necessary without having to restart your system. This will remain RED at all times except when we are updating your license.

[Return to Contents](#)

Telephony Server (PBX)

This is the communication portal for the Media Gateway.

[Return to Contents](#)

Media Gateway

This is the portion of the software that runs the different licensed features tied to the MediaGateway such as Two-way voice, OpenVoice, Direct Connect, and the like.

[Return to Contents](#)

Location Server

Utilizes GPS to determine the alarm location then presents applicable PSAP (Authority) details within the alarm.

[Return to Contents](#)